

## A25 SERIES

### PM2.5 Meters

A25 series air quality meters are used to measure PM2.5 concentration. A25 series can be used in homes, offices, hotels, schools, factories, hospitals, restaurants, and other public places.

- Precise PM2.5 concentration based on pre-calibrated sensors
- Temperature measurement (°C/°F)
- Humidity measurement (A25D)
- Emoticon display
- LCD backlight and red backlight alarm
- Battery status, low power, auto power off



● A25M



● A25D

	Range	A25M	A25D
Certificates	CE, RoHS		
PM2.5 (ug/m <sup>3</sup> )	0~100	±(10ug/m <sup>3</sup> +10dgts)	±(10ug/m <sup>3</sup> +10dgts)
	101~400	±(10%+30dgts)	±(10%+30dgts)
	401~500	±(10%+50dgts)	±(10%+50dgts)
Formaldehyde (mg/m <sup>3</sup> )	0~2		
Temperature	-10°C~50°C	For reference only	±1°C
Humidity	5%~99%RH		±5%RH@30%~80%RH ±8%RH@<30%RH, >80%RH
Power	A25M: 520mAh Li-ion battery; A25D: 1500mAh Li-ion battery		
Display	A25M: 35mm x 35mm; A25D: 42mm x 65mm		
Product net weight	A25M: 85g; A25D: 230g		
Product size	A25M: 64mm x 60mm x 28mm; A25D: 75mm x 55mm x 130mm		
Standard accessories	1m micro USB cable, wall mount (A25M), English manual		
Standard individual packing	Gift box		
Standard quantity per carton	A25M: 20pcs; A25D: 5pcs		
Standard carton measurement	A25M: 325mm x 215mm x 210mm; A25D: 360mm x 185mm x 140mm		
Standard carton gross weight	A25M: 4.5kg; A25D: 2.35kg		