



● UT332

UT330 series meters measure temperature and humidity with low power consumption and high precision. The measured data can be saved and exported to PC software for further analysis. These meters can be used in factories, laboratories, research institutes, food, health, environmental protection, and other fields.



### SPECIFICATIONS

			UT331	UT332
Temperature	Range	-20°C~70C (-4°F~158°F)	√	√
	Accuracy	-20°C~0°C	±1°C	±1°C
		0°C~40°C	±0.5°C	±0.5°C
		40°C~70°C	±1°C	±1°C
Resolution	0.1°C/0.1°F	√	√	
Humidity	Range	0%RH~100%RH	√	√
	Accuracy	10%RH~90%RH	±3.5%RH	±2.5%RH
		<10%RH or >90%RH	±5%RH	±5%RH
	Resolution	0.1%RH	√	√

#### Features

°C/°F selection		√	√
Response time	Around 10 seconds	√	√
Humidity offset settings		√	√
Temperature offset settings		√	√
Dew point offset settings		√	√
Auto power off		√	√
Power saving mode			√
Data hold		√	√
MAX/MIN		√	√
Data storage		√	√
Data recall		√	√
USB interface		√	√
Auto record time setup		√	√
LCD backlight		√	√

### GENERAL CHARACTERISTICS

Power	1.5V battery (R03) x 4
Display	26.5mm x 35.5 mm
Product color	Red and grey
Product net weight	130g
Product size	185mm x 54.8mm x 33.8mm
Standard accessories	Batteries, carrying bag, PC software CD, USB interface cable
Standard individual packing	Gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	430mm x 290mm x 290mm
Standard carton gross weight	6.3kg