

# UT300A+

## Infrared Thermometer

- Temperature range: -20°C~400°C
- Simple one button operation
- 10:1 D:S ratio
- Data hold
- Backlight
- Low battery indication
- °C/°F selection



● UT300A+

SPECIFICATION	UT300A+
Certificates	CE, RoHS
Temperature range (°C)	-20°C~400°C
Temperature range (°F)	-4°F~752°F
Accuracy (°C)	±2.0°C or ±2%
Accuracy (°F)	±4.0°F or ±2%
Repeatability	1°C or 1.0% (2°F or 1.0%)
D:S ratio	10:1
Response time	≤500ms (95% of reading)
Emissivity	0.95
Spectral response	5.5um~14um
Laser power	< 1mW
Auto power off	8s
Operating temperature	0°C~50°C (32°F~122°F)
Storage temperature	-20°C~60°C (-4°F~140°F)
Operating humidity	<90% RH (non-condensing)
Drop proof	1m
GENERAL CHARACTERISTICS	
Power	1.5V battery (LR03) x 2
Display	20mm x 24mm
Product net weight	146g
Product size	135mm x 94mm x 36.5mm
Standard accessories	Gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	430mm x 265mm x 300mm
Standard carton gross weight	6.97kg