

# UT306A


## Mini Infrared Thermometer

UT306A is a portable non-contact thermometer. This device's miniature design is convenient to carry and suitable for everyday temperature measurement needs. UT306A is designed to counter environmental interference, ensuring accurate temperature readings under various measurement environments.

- Auto power off
- Low battery indication
- Data hold
- °C/°F selection
- MAX/MIN/AVG mode
- Lock measurement
- Backlight
- Laser on/off



● UT306A



SPECIFICATION	UT306A
Certificates	CE, RoHS
Temperature range (°C)	-35°C~300°C
Temperature range (°F)	-31°F~572°F
Accuracy (°C)	±2°C or ±2%
Accuracy (°F)	±4°F or ±2%
D:S ratio	6:1
Response time	<250ms
Emissivity	0.95
Spectral response	8um~14um
Laser power	<1mW
Operating temperature	0°C~50°C (32°F~104°F)
Storage temperature	-20°C~60°C (-4°F~140°F)
Operating humidity	<90%RH (non-condensing)
Drop proof	1m
GENERAL CHARACTERISTICS	
Power	1.5V battery (R03) x 3
Display	37.4mm x 36.4mm
Product net weight	120g
Product size	120mm x 53mm x 28mm
Standard accessories	Batteries, English manual
Standard individual packing	Gift box
Standard quantity per carton	20pcs
Standard carton measurement	272mm x 225mm x 200mm
Standard carton gross weight	2.8kg